

LT-TELT-1L

Tactical Telephone

Our LT-TELT-1L field telephone is mainly used for field or indoor wire communication. It is designed with five operation modes: local battery, central battery (CB), Auto (Pulse, DTMF) and local battery DTMF (LB DTMF).

Features

- When using “Loud” switch in LB or LB DTMF mode, the communication range can reach to 38 km.
- Stable and reliable performance, clear voice and good electromagnetic compatibility.
- Immersible, shock-resistant and drop-resistant.
- Good applicability, utilized in LB, Auto and private switched network.
- Good mobility and full function.



Specifications

Ambient Conditions	
Operating Temperature	LB: -40 °C to +60 °C Auto/CB: - 30 °C to +60°C
Relative Humidity	≤ 95% at +40 °C
Air Pressure	70 kPa to 106 kPa
Noise	1.0 (0.45)

Power	
Local Battery	LB: -40 °C to +60 °C Auto/CB: - 30 °C to +60°C
Auto/CB	24 V to 60 V Feeding Current 18 mA to 80 mA
Air Pressure	70 kPa to 106 kPa

Ringing	
Current	430 mA
Voltage	≥ 55V rms into 3k Ohms
Frequency	16 Hz to 30 Hz
Ringing Duration	1s to 1.5s each time

Physical Specifications	
Dimensions	252 x 142 x 103 mm
Weight	1.95 Kg excluding battery