

Drill Driver LXT®

DDF446RFE

14,4V • 44 Nm • 0 - 1 500 min⁻¹

Small and light screwdriver for multiple applications

A general-use tool with two speed ranges for screwdriving and drilling. Max. torque of 44 / 30 Nm. Suitable for light professional use or demanding amateur use. Includes 2 x 3,0 Ah batteries and a charger.



TECHNICAL SPECIFICATIONS

Vibration Level, Drilling into metal	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor), Drilling into metal	1,5 m/s ²
Voltage LXT	✓
Nominal Battery Voltage	14,4 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 400 / 0 - 1500 min ⁻¹
Max. fastening torque Hard/Soft	44 / 30 Nm
Torque setting	16
Max. Drilling Diameter in Wood	38 mm
Drilling Capacity Wood (Auger Bit)	38 mm
Drilling Capacity Wood (Self-feed bit)	76 mm
Max. Drilling Diameter in Steel	13 mm
Driving Shank	1/2"-20UNF "
Drill Chuck Capacity	1,5 - 13 mm
Sound Pressure Level (L _{pA})	71 dB(A)

USER BENEFITS

- LED light illuminates the work site

EAN 0088381669078

Link to Product page - www.makita.ae



RELATED PRODUCTS

■ STANDARD MACHINES

195584-2

Battery Charger LXT®, Li-ion, 14,4 -



■ OPTIONAL ACCESSORIES

821550-0

Makpac case (2)



■ OTHER

User manual

