

Drill Driver G-series DF347DWE

14,4V • 30 Nm • 0 − 1 400 min⁻¹

For screwdriving and drilling in two speed

A general-use tool with two speed ranges for screwdriving and drilling. Max. torque of 30 / 15 Nm. Suitable for light professional use or demanding amateur use. Uses G-batteries and they are not compatible with the Makita LXT® range of cordless tools or chargers. Includes 2 x 1.5Ah G-series batteries and a charger.



14.4V

TECHNICAL SPECIFICATIONS

Vibration Level, Drilling into metal $\leq 2.5 \text{ m/s}^2$ Vibration Uncertainty (K Factor), 1,5 m/s² Drilling into metal

G-series √
Nominal Battery Voltage 14,4 V

Battery Chemistry (Ni-Cd / Ni-MH / Li-Li-ion

No load speed 0 - 400 / 0 - 1400

min⁻¹
Max. fastening torque Hard/Soft 30 / 15 Nm

Torque setting 16

Max. Drilling Diameter in Wood 25 mm

Max. Drilling Diameter in Steel 10 mm

Driving Shank 3/8 "

Drill Chuck Capacity 0,8 - 10 mm
Tool weight with battery 1,4 - 1,5 kg

Product Dimensions (L x W x H): 198 x 83 x 235 mm

Plastic Carrying Case

USER BENEFITS

- The rubber coating on the handle ensures a firm working grip
- Single sleeve keyless chuck enables easy bit installation/removal with one hand
- Weight only 1.4 kg



EAN 0088381616683

Link to Product page - www.makita.ae





RELATED PRODUCTS

STANDARD MACHINES

195423-6

Battery Charger G-series, 14,4 - 18V,



198192-8 (2x)Battery G-Seriers 1,5 Ah, Li-ion,





User manual

