Magnetic drill

ECO-TUBE.30



30_{mm}

11











532

90_{mm}

Features

- No electricity required for magnetic base
- Unique flexible features for pipes of various sizes
- · No special attachments needed to accommodate flat or curved surfaces
- · Highly stable wide stance
- Two separate magnets which allows the machine to swing away for hole inspection & debris removal without losing position
- Easy to handle
- Direct spindle drive

The ECO-TUBE.30 with patented shallow-field magnetic technology that offers incredibly strong grip, even on steel as thin as 3mm. Also, the patentpending base automatically pivots to conform to any pipe Ø 75mm or larger. The magnets do not require electricity, so all the power goes to the motor. This also offers increased safety as the tool will not release from the target material in the event of an unintentional power loss. With its 900W power the ECO-TUBE.30 cuts holes between Ø 12 and 30mm easily and quickly.

Technical data

ECO-TUBE.30

Ø 12 - 30 mm Annular cutters Twist drills Ø 1 - 13 mm Countersinking Ø 10 - 35 mm Length 275 mm Width 185 mm Height 326 - 416 mm Stroke 90 mm Weight 11 kg

Magnet (I x w x h) 187 x 165 x 83 mm

Magnetic force 532 kg Motor power 900 W Total power 950 W Speed (no load) 775 min⁻¹ Speed (load) 400 min⁻¹

Spindle 19.05 mm Weldon

110-120 / 220-240 V / 50-60 Hz Power source











FOR PROFESSIONALS BY PROFESSIONALS