

Weldon twist drills

HSS 19.05 mm (3/4") Weldon shank. 135° split point. Available in 30 mm, 50 mm length, 1" and 2" (DoC).

Machined from one solid blank (no weak spots caused by inferior material or welds).

DoC 30 mm
DIA Ø 6 - 14 mm

MM	Code
Ø 6	SSPI.06
Ø 7	SSPI.07
Ø 8	SSPI.08
Ø 9	SSPI.09
Ø 10	SSPI.10
Ø 11	SSPI.11
Ø 12	SSPI.12
Ø 13	SSPI.13
Ø 14	SSPI.14

DoC 1"
DIA Ø 1/4" - 9/16"

INCH	Code
Ø 1/4"	SSPI.1/4"
Ø 5/16"	SSPI.5/16"
Ø 3/8"	SSPI.3/8"
Ø 7/16"	SSPI.7/16"
Ø 1/2"	SSPI.1/2"
Ø 9/16"	SSPI.9/16"



- 6 piece Weldon twist drill set**
- HSS 19.05 mm (3/4") Weldon shank
 - 135° split point
 - 30 mm length (DoC)
 - Sizes Ø 6 - 11 mm, 1 mm increments

SSPI.KIT

DoC 50 mm
DIA Ø 6 - 14 mm

MM	Code
Ø 6	SPI.06
Ø 7	SPI.07
Ø 8	SPI.08
Ø 9	SPI.09
Ø 10	SPI.10
Ø 11	SPI.11
Ø 12	SPI.12
Ø 13	SPI.13
Ø 14	SPI.14

DoC 2"
DIA Ø 1/4" - 9/16"

INCH	Code
Ø 1/4"	SPI.1/4"
Ø 5/16"	SPI.5/16"
Ø 3/8"	SPI.3/8"
Ø 7/16"	SPI.7/16"
Ø 1/2"	SPI.1/2"
Ø 9/16"	SPI.9/16"



- 6 piece Weldon twist drill set**
- HSS 19.05 mm (3/4") Weldon shank
 - 135° split point
 - 50 mm length (DoC)
 - Sizes Ø 6 - 11 mm, 1 mm increments

SPI.KIT

Countersinks

- HSS 19.05 mm (3/4") Weldon shank
- 3 cutting edges
- 90°

Weldon countersinks

MM	Code
Ø 10 - 25	SCE.25
Ø 10 - 40	SCE.40
Ø 15 - 50	SCE.50



Straight shank countersinks

MM	Code
Ø 6.3	CSB.63
Ø 8.3	CSB.83
Ø 10.4	CSB.104
Ø 12.4	CSB.124
Ø 16.5	CSB.165
Ø 20.5	CSB.205

- 6 piece straight shank countersink set**
- Sizes Ø 6.3 - 8.3 - 10.4 - 12.4 - 16.5 - 20.5 mm
 - HSS-Cobalt (M35 quality) straight shank
 - Compatible with every drill chuck
 - 3 cutting edges
 - 90°

CBS.620

